

1 **MOBILE BASE**

2 **BACKGROUND OF THE INVENTION**

3 **1. Field of the Invention**

4 The present invention relates to a mobile base, and more particularly  
5 to a mobile base for a miniature tool, such as a small-size sawing table, a  
6 small-size tool machine or the like.

7 **2. Description of the Related Art**

8 A conventional base 12 in accordance with the prior art shown in  
9 Figs. 6 and 7 is used to support a small-size sawing table 10 and comprises four  
10 upright posts 122, four upper transverse bars 14 mounted between upper  
11 portions of the four upright posts 122, and four lower transverse bars 16  
12 mounted between lower portions of the four upright posts 122. However, the  
13 conventional base 12 is fixed and cannot be moved easily, thereby causing  
14 inconvenience to the user when he wishes to move the conventional base 12. In  
15 addition, the conventional base 12 has a complicated construction with more  
16 parts, thereby increasing time of assembly and disassembly, and thereby  
17 causing inconvenience to the user when mounting the conventional base 12.

18 The closest prior art references of which the applicant is aware are  
19 disclosed in U.S. Patent No. 5,431,254, U.S. Patent No. 5,903,956, and U.S.  
20 Patent No. 6,109,625.

21 **SUMMARY OF THE INVENTION**

1           The primary objective of the present invention is to provide a mobile  
2 base for a miniature tool, such as a small-size sawing table, a small-size tool  
3 machine or the like.

4           Another objective of the present invention is to provide a mobile  
5 base that has a simplified construction with fewer parts, thereby saving time of  
6 assembly and disassembly, and thereby facilitating the user mounting the  
7 mobile base.

8           A further objective of the present invention is to provide a mobile  
9 base that is assembled by a first side rack, a second side rack, a plurality of  
10 upper transverse bars, and a plurality of lower transverse bars, so that the  
11 mobile base has a rigid and stable structure.

12           A further objective of the present invention is to provide a mobile  
13 base, wherein the adjusting roller is hidden in the respective lower transverse  
14 bar, and the adjusting unit is hidden in a space between the first side rack and  
15 the second side rack, so that the adjusting unit is not operated unintentionally.

16           In accordance with the present invention, there is provided a mobile  
17 base, comprising:

18           a main body having a first side formed with two first foot portions  
19 and a second side formed with two second foot portions;

20           two fixing rollers each mounted on a respective one of the two first  
21 foot portions of the main body;

1           an adjusting plate mounted between the two second foot portions of  
2 the main body;

3           an adjusting roller mounted on the adjusting plate to move therewith;  
4 and

5           an adjusting unit mounted between the two second foot portions of  
6 the main body and urged on the adjusting plate to press the adjusting plate to  
7 move toward a ground and to move outward relative to the ground.

8           Further benefits and advantages of the present invention will become  
9 apparent after a careful reading of the detailed description with appropriate  
10 reference to the accompanying drawings.

#### 11           **BRIEF DESCRIPTION OF THE DRAWINGS**

12           Fig. 1 is a perspective view of a mobile base in accordance with the  
13 preferred embodiment of the present invention;

14           Fig. 2 is an exploded perspective view of the mobile base in  
15 accordance with the preferred embodiment of the present invention;

16           Fig. 3 is a partially exploded perspective view of the mobile base in  
17 accordance with the preferred embodiment of the present invention;

18           Fig. 4 is a plan cross-sectional operational view of the mobile base in  
19 accordance with the preferred embodiment of the present invention;

20           Fig. 5 is a plan cross-sectional operational view of the mobile base in  
21 accordance with the preferred embodiment of the present invention;

1           Fig. 6 is a perspective view of a conventional base for a small-size  
2   sawing table in accordance with the prior art; and

3           Fig. 7 is an exploded perspective view of the conventional base for a  
4   small-size sawing table in accordance with the prior art.

### 5           **DETAILED DESCRIPTION OF THE INVENTION**

6           Referring to the drawings and initially to Figs. 1-3, a mobile base 30  
7   in accordance with the preferred embodiment of the present invention is used  
8   to support a small-size sawing table 90 and comprises a first side rack 50, a  
9   second side rack 60, a plurality of upper transverse bars 72 mounted between  
10   the first side rack 50 and the second side rack 60, and a plurality of lower  
11   transverse bars 38 mounted between the first side rack 50 and the second side  
12   rack 60.

13          The first side rack 50 has a first side formed with a first leg 52 having  
14   a lower end formed with a first foot portion 522 provided with a fixing roller  
15   36 and a second side formed with a second leg 54 having a lower end formed  
16   with a second foot portion 542. The first side rack 50 includes a plurality of  
17   transverse portions 56 mounted between the first leg 52 and the second leg 54.

18          The second side rack 60 has a first side formed with a first leg 62  
19   having a lower end formed with a first foot portion 622 provided with a fixing  
20   roller 36 and a second side formed with a second leg 64 having a lower end  
21   formed with a second foot portion 642. The second side rack 60 includes a

1 plurality of transverse portions 66 mounted between the first leg 62 and the  
2 second leg 64.

3 In practice, the first foot portion 522 of the first leg 52 of the first side  
4 rack 50 is provided with the fixing roller 36, and the first foot portion 622 of  
5 the first leg 62 of the second side rack 60 is also provided with the fixing roller  
6 36, so that the first foot portion 522 of the first side rack 50 and the first foot  
7 portion 622 of the second side rack 60 are defined to be located at the same side.  
8 Similarly, the second foot portion 542 of the first side rack 50 and the second  
9 foot portion 642 of the second side rack 60 are defined to be located at the same  
10 side.

11 In addition, the mobile base 30 further comprises a support tray 74  
12 mounted on the first side rack 50 and the second side rack 60 to support the  
13 small-size sawing table 90.

14 In addition, the mobile base 30 further comprises an adjusting plate  
15 48 mounted on the respective lower transverse bar 38, and an adjusting roller  
16 46 mounted on the adjusting plate 48 to move therewith. Preferably, the  
17 adjusting plate 48 is made of elastic material and has a bent structure.

18 In addition, the mobile base 30 further comprises an adjusting unit 40  
19 mounted on a respective lower transverse bar 38 located between the second  
20 foot portion 542 of the first side rack 50 and the second foot portion 642 of the  
21 second side rack 60. The adjusting unit 40 is a lever mechanism and includes a  
22 cam 42 pivotally mounted on the respective lower transverse bar 38 and rested

1 on the adjusting plate 48, and an operation handle 44 mounted on the cam 42 to  
2 drive the cam 42 to pivot on the respective lower transverse bar 38.

3 The cam 42 is pivotally mounted on the respective lower transverse  
4 bar 38 by a pivot shaft 45. The respective lower transverse bar 38 is formed  
5 with an elongated slot 382, and the cam 42 is extended through the elongated  
6 slot 382 of the respective lower transverse bar 38. The cam 42 has a first side  
7 formed with a first urging face 422 and a second side formed with a second  
8 urging face 424. The first urging face 422 and the second urging face 424 of the  
9 cam 42 are oblique and are directed toward different directions. The first  
10 urging face 422 and the second urging face 424 of the cam 42 are juxtaposed to  
11 each other.

12 In operation, referring to Figs. 4 and 5 with reference to Figs. 1-3,  
13 when the operation handle 44 of the adjusting unit 40 is pulled to move  
14 outward relative to the adjusting plate 48, the cam 42 is pivoted relative to the  
15 adjusting plate 48 to move to the position as shown in Fig. 4 where the first  
16 urging face 422 of the cam 42 is spaced from the adjusting plate 48, so that the  
17 adjusting plate 48 is moved upward by its elastic force to move the adjusting  
18 roller 46 upward to locate the adjusting roller 46 at a level higher than that of  
19 the second foot portion 542 of the first side rack 50 and the second foot portion  
20 642 of the second side rack 60. Thus, the adjusting roller 46 is spaced from the  
21 ground so that the base 30 is fixed on the ground by the drag effect of the

1 second foot portion 542 of the first side rack 50 and the second foot portion  
2 642 of the second side rack 60.

3           Alternatively, when the operation handle 44 of the adjusting unit 40  
4 is pushed to move toward the adjusting plate 48, the cam 42 is pivoted relative  
5 to the adjusting plate 48 to move to the position as shown in Fig. 5 where the  
6 second urging face 424 of the cam 42 is urged on the adjusting plate 48, so that  
7 the adjusting plate 48 is moved downward to move the adjusting roller 46  
8 downward to locate the adjusting roller 46 at a level lower than that of the  
9 second foot portion 542 of the first side rack 50 and the second foot portion  
10 642 of the second side rack 60. Thus, the adjusting roller 46 is rested on the  
11 ground so that the base 30 is movable on the ground by co-operation of the  
12 adjusting roller 46 and the two fixing rollers 36.

13           Accordingly, the mobile base 30 has a simplified construction with  
14 fewer parts, thereby saving time of assembly and disassembly, and thereby  
15 facilitating the user mounting the mobile base 30. In addition, the mobile base  
16 30 is assembled by a first side rack 50, a second side rack 60, a plurality of  
17 upper transverse bars 72, and a plurality of lower transverse bars 38, so that the  
18 mobile base 30 has a rigid and stable structure. Further, the adjusting roller 46 is  
19 hidden in the respective lower transverse bar 38, and the adjusting unit 40 is  
20 hidden in a space between the first side rack 50 and the second side rack 60, so  
21 that the adjusting unit 40 is not operated unintentionally.

1           Although the invention has been explained in relation to its preferred  
2   embodiment(s) as mentioned above, it is to be understood that many other  
3   possible modifications and variations can be made without departing from the  
4   scope of the present invention. It is, therefore, contemplated that the appended  
5   claim or claims will cover such modifications and variations that fall within the  
6   true scope of the invention.